2018-2024 Alfa Romeo Stelvio - Engine Oil & Filter

2018-2024 Alfa Romeo Stelvio | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (0W-30) $45.00
Correct engine oil filter and drain-plug washer for 2018-2024 Alfa Romeo Stelvio $12.00

STEPS

1. **Confirm the Stelvio’s oil spec and gather supplies - 2.0L turbo (GME T4): 5.5 quarts** (5.2L) 0W-30 meeting FCA MS-13340 - no generic 0W-30. Gather cartridge element, fresh O-rings, new washer, drain pan. Park level, brake set, chock wheels; raise front on ramps or stands.
2. **Remove the undertray and locate the housing - Warm briefly, shut off. Cartridge housing** at the engine’s FRONT - remove the undertray to reach it from below; drain plug on the pan bottom. Pan under the plug. The undertray mixes screws and quarter-turn fasteners - keep them sorted.
3. **Drain the oil and replace the cartridge - Pull the plug; drain fully. Meanwhile unscrew** the front housing cap, lift the old element, replace the O-rings pre-lubed with fresh oil. Seat the new element; refit the cap. Torque cap and plug per the manual.
4. **Reinstall, refill, and check the dipstick - Refit the plug with a fresh washer; refit the** undertray. Lower to level; pour 5.5 quarts MS-13340 0W-30 through the valve-cover filler. Wait a few minutes, dipstick, add small amounts to full.
5. **Check for leaks and reset the reminder - Run 30 seconds; check plug and housing for** leaks. Off, wait two minutes, recheck dipstick. Reset the reminder via infotainment. Quadrifoglio (2.9L): 7.2 quarts, not 5.5. Gas-smelling oil means fuel dilution - shorten the interval.

TORQUE

ezcarfix.com