2016-2024 BMW M2 Competition - Replace Front Rotors

2016-2024 BMW M2 | Advanced | 2-3 hours | $775 DIY

TOOLS

10mm Socket 17mm Socket Torque Wrench Jack Stands Flathead Screwdriver Rubber Mallet Brake Fluid Brake Cleaner C-Clamp Lug Wrench

PARTS

Front Brake Rotors 34118072017/34118072018 $625.00
Front Brake Pads 34112284869 $150.00

STEPS

1. **Loosen lugs and support the vehicle - On level ground, crack the front lug nuts loose on** the 2016-2024 BMW M2 Competition. Chock the rear wheels, jack the front at the approved lift point, and support with jack stands before removing the wheel. Wear gloves and eye protection ...
2. **Remove the caliper and bracket - Remove the caliper slide bolts and hang the caliper with** a hook/wire - do not let it dangle by the brake hose on the 2016-2024 BMW M2 Competition. Remove the caliper bracket bolts and set the bracket aside.
3. **Remove the old rotor - Remove any retainer screws or rust clip holding the rotor to the** hub. If the rotor is stuck, apply penetrant and tap from behind with a rubber mallet - never strike the 2016-2024 BMW M2 Competition wheel studs.
4. **Clean the hub and install the new rotor - Clean the new rotor’s faces with brake cleaner** to remove packing oil. Seat the new rotor on the 2016-2024 BMW M2 Competition hub and reinstall any retainer screws.
5. **Reinstall the bracket and pads; reconnect the wear sensors - Reinstall the caliper** bracket and torque to spec. Install pads (replace if worn or contaminated) with correct shims/grease on contact points only. Reconnect pad wear sensors on the 2016-2024 BMW M2 Competition.
6. **Torque wheels, bed the brakes, and check - Reinstall the wheel, lower the 2016-2024 BMW** M2 Competition, and torque lugs in a star pattern. Bed the new rotors/pads with several moderate decelerations from ~30-40 mph per the pad maker’s procedure.

ezcarfix.com