2013-2019 Cadillac ATS - Engine Oil & Filter Change

2013-2019 Cadillac ATS | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2013-2019 Cadillac ATS $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - The 2.0L turbo LTG takes 5.0 quarts** of dexos1 5W-30 (3.6L V6: 6.0; 2.5L: 5.0 - confirm your engine). The 2.0T/3.6L use a PF64-type cartridge in a top-side housing. Park level, brake set; gather the cartridge, O-ring, and drain pan.
2. **Warm briefly and protect the work area - Idle a few minutes so the oil drains fully, then** switch off and remove the filler cap. The cartridge housing is top-side - no undertray work. Raise front on ramps or stands with a 6-quart pan under the oil pan.
3. **Drain the used oil and replace the cartridge filter - Pull the drain plug, drain to a** drip, and refit with a fresh washer, tightened firmly. Loosen the top-side housing cap, swap the cartridge, seating the oiled O-ring in the cap groove, then reinstall the cap without overtightening the plast...
4. **Install the correct oil quantity - Pour 5.0 quarts of dexos1 5W-30 through a funnel (6.0** for the 3.6L V6). Add about 4.5 quarts first, wait a minute, then top up gradually to the full mark. Refit the filler cap and wipe the valve cover.
5. **Check level, leaks, and service reminder - Idle a minute so the new filter fills and the** oil light goes out. Shut off, wait a few minutes, and recheck the dipstick. Check the plug and housing for leaks. Reset the oil-life monitor per the owner’s manual.

TORQUE

ezcarfix.com