2011-2014 Cadillac CTS-V - Engine Oil & Filter

2011-2014 Cadillac CTS-V | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2011-2014 Cadillac CTS-V Wagon $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - The 2011-2014 CTS-V's supercharged** LSA 6.2L V8 holds 6 US quarts of 5W-30 meeting the dexos1 standard. It uses a traditional spin-on filter - AC Delco PF48 is the catalog listing. The drain plug size and torque weren't independently veri...
2. **Warm briefly and protect the work area - Warm the engine 2-3 minutes -- warm oil drains** faster from the LSA's big sump. Gather a large drain pan (6+ quarts), funnel, filter wrench, and gloves, and raise the front on ramps or jack stands.
3. **Drain the used oil and replace the filter - Remove the drain plug and drain fully.** Compare old and new filters (PF48 or equivalent) and verify the old gasket came off with the old filter.
4. **Install the correct oil quantity - Pour in 6 quarts of 5W-30 dexos1 oil through a funnel** in the filler neck -- add the last quart slowly so the funnel does not back up.
5. **Check level, leaks, and service reminder - Start the engine, idle 30-60 seconds, and** check the filter and drain plug for leaks. Reset the oil life monitor, and recycle the used oil and filter. If you do lift it, use rated jack stands - and keep oil off the tires and ground.

TORQUE

ezcarfix.com