2003-2007 Cadillac CTS - Cabin Air Filter

2003-2007 Cadillac CTS | Easy | 20-30 minutes | $20 DIY

TOOLS
Screwdriver or trim tool Rags

PARTS
Cabin air filter $20.00

STEPS

1. **Open the hood and find the filter access - With the ignition off, open the hood of the** CTS. Clear any leaves from the cowl area first.
2. **Remove the cowl cover fasteners - Locate the plastic access cover over the filter housing** at the passenger-side cowl. Remove its screws or plastic push-pins with a screwdriver or trim tool. Lift the cover off and set it aside where it will not blow away.
3. **Pull the old filter - Lift the old cabin filter straight out of its tray, noting the** airflow arrow direction. Clean the tray and the surrounding cowl drain area so water flows away properly.
4. **Install the new filter - Set the new filter into the tray with the airflow arrow pointing** the correct direction (down into the intake). Press it flat so it seals around all edges.
5. **Reinstall the cover and test - Replace the cowl cover and secure all its fasteners so it** seals against the windshield base. Close the hood. Start the car, run the blower on high, and confirm strong airflow without rattling leaves in the dash.
6. **Clear the cowl drains - While the cover is off, check that the cowl drain holes at the** base of the windshield are not clogged with leaves. Pour a small cup of water into the cowl and confirm it drains freely underneath the car.

ezcarfix.com