2019-2024 Chevrolet Blazer - Oil Change

2019-2024 Chevrolet Blazer | Moderate | 45 minutes | $40 DIY

TOOLS

15mm Socket Flathead Screwdriver Jack Stands Oil Filter Wrench Drain Pan Torque Wrench Funnel

PARTS

Engine Oil (5W-30 Full Synthetic) $30.00
Oil Filter $10.00

STEPS

1. **Prepare (5W-30 Dexos1, 6.0 qt!) - The 2019-2024 Blazer (3.6L LGX V6) takes 5W-30 full** synthetic Dexos1 Gen3, 6.0 quarts (5.7L) with filter - buy 7 quarts. You'll need: new filter (GM 19330000 or equivalent), drain pan, funnel. Park on level ground.
2. **Drain the Old Oil - Position the drain pan under the drain plug and remove it, letting** the old 5W-30 drain (expect ~6.0 quarts). The LGX is easy on oil, but keep to the Dexos1 Gen3 spec.
3. **Replace Oil Filter - Remove the old oil filter. Install the new one (GM 19330000 or** equivalent) - hand-tighten plus a quarter turn - and make sure the old gasket came off with the old filter.
4. **Reinstall Drain Plug (18 ft-lbs) - Reinstall the drain plug and torque to 18 ft-lbs - use** a torque wrench and don't over-tighten. The LGX's 18 ft-lbs is a light spec; stripping the threads is the expensive mistake.
5. **Add 6.0 Quarts of 5W-30 - Add 6.0 quarts (5.7L) of 5W-30 Dexos1 Gen3 full synthetic** through the filler. Use ONLY Dexos1 Gen3-approved 5W-30 - not 0W-20, which is for the V8 trucks. Check the dipstick.
6. **Check Level, Leaks, Reset Monitor - Start the engine and check for leaks, then recheck** the oil level after 30 seconds and top up if needed. Reset the oil life monitor. Interval: follow the monitor, typically 7,500 miles.

TORQUE

Oil Drain Plug 25 Nm 18 ft-lbs
Oil Filter Housing 25 Nm 18 ft-lbs

ezcarfix.com