2011-2017 Chevrolet Caprice - Engine Oil & Filter

2011-2017 Chevrolet Caprice | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels 15mm Socket

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2011-2017 Chevrolet Caprice $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - Gather 8.0 quarts of full-synthetic** 5W-30, an ACDelco PF48/PF48E spin-on filter, a 9-quart drain pan, funnel, gloves, a 15mm socket, and a filter wrench. Park level, chock the rear wheels, and raise the front onto jack stands or ramps.
2. **Warm briefly and protect the work area - Idle 2-3 minutes so the oil drains fast, then** shut off before the exhaust gets hot. Remove the filler cap and lift the dipstick to vent the crankcase. Position the drain pan under the pan and spread cardboard for drips.
3. **Drain the used oil and replace the filter - Crack the drain plug on the oil pan (a 15mm** socket fits the L77's M12 plug - confirm fit) and spin it out by hand over the large drain pan; eight quarts comes out fast. The spin-on filter (ACDelco PF48/PF48E type) screws onto the driver'...
4. **Install the correct oil quantity - Set a funnel in the filler neck and pour in 8.0 quarts** of full-synthetic 5W-30. Pour slowly and watch the markings - adding a final half-quart later beats draining an overfill.
5. **Check level, leaks, and service reminder - Idle one minute, watching the plug and filter** area for leaks, then shut off and wait two minutes. Top up if below the full mark. Reset the oil-life monitor through the driver information center; recycle the used oil.

TORQUE

ezcarfix.com