2010-2017 Chevrolet Equinox 2.4L - Heater Blower

2010-2017 Chevrolet Equinox | Moderate | 45 minutes | $85 DIY

TOOLS

1/4 Inch Ratchet Gloves Socket Extensions 1/4 Inch Socket 7mm Socket Trim Tool Set Safety Glasses

PARTS

Blower Motor TRQ HMA84805 $84.95

STEPS

1. **Disconnect the battery and access the blower - Disconnect the negative battery cable.** Wear gloves; sharp sheet-metal edges are common.
2. **Unplug the blower and note the resistor/module - Unplug the blower motor connector. If a** blower resistor or control module is attached inline, note its orientation and whether it shares screws with the motor cover. Inspect for heat damage or water intrusion.
3. **Remove the blower motor assembly - On the 2010-2017 Chevrolet Equinox 2.4L: remove the** retaining screws and lower the blower motor out of the housing. Catch any debris or leaves that fall from the scroll. Do not bend the fan cage.
4. **Compare the new motor and clean the housing - Match connector style, cage diameter, and** mounting flange to the old motor. Vacuum leaves and dust from the HVAC housing opening so the new cage does not hit debris. Transfer any foam seals if not included on the new unit.
5. **Install the new blower and reconnect - Seat the new blower so the cage clears the** housing, install screws evenly, and reconnect the electrical connector. Reinstall trim panels. Reconnect the battery negative cable.
6. **Test all speeds and listen for noise - Key-on and run the Chevrolet Equinox blower** through all speeds in vent mode. Confirm strong airflow with no scraping, squeal, or intermittent cut-out. Recheck dash panels for rattles after a short drive.

ezcarfix.com