2012-2014 Chevrolet Orlando - Cabin Air Filter

2012-2014 Chevrolet Orlando | Easy | 15-20 minutes | $28 DIY

TOOLS
No tools required - hands only Damp rag or vacuum Torch or headlamp

PARTS
Cabin air filter for 2012-2014 Chevrolet Orlando; verify arrows, size, and VIN/trim fitment $28.00

STEPS

1. **Set up: empty the glove box - The Orlando’s cabin filter sits behind the glove box on the** passenger side, and the whole glove-box bin has to come out. Not just swing down, but lift out entirely and set on the floor.
2. **Release the side walls and swing the bin down - Open the glove box and press firmly on** both side walls in the direction of the arrows, bending them inward so the retaining lugs clear. The bin swings down past its normal open position. Don’t be gentle about it.
3. **Disconnect the damper arm and lift the bin out - Important: don’t let the damper arm snap** back and disappear into the dash opening - hold it or clip it aside, because fishing a retracted damper out of the dash is miserable.
4. **Open the three plastic clasps on the filter cover - With the bin out of the way you’ll** see the filter housing with its cover held by three plastic clasps. The clasps are the only thing holding it. There are no screws. Keep your fingers clear of the blower opening as the cover comes free.
5. **Slide the old filter out - Slide the old filter element straight out of the housing. Keep** it over the footwell as you pull it so the debris doesn’t scatter across the dashboard trim.
6. **Clean the housing and slide in the new filter - Wipe or vacuum the inside of the housing.** Orlando filters pick up a surprising amount of grit behind the glove box. Push it fully home, then swing the cover up and snap all three clasps shut.
7. **Refit the glove box and test - Lift the glove-box bin back onto its hinges, reconnect the** damper arm so the box opens with its normal soft motion, then push the side walls inward and swing the bin up until the lugs click back into place. Close the box and make sure it l...

TORQUE

ezcarfix.com