2012-2014 Chevrolet Orlando - Engine Oil & Filter

2012-2014 Chevrolet Orlando | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2012-2014 Chevrolet Orlando $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - The exact filter wasn’t** independently verifiable - confirm it in your owner’s manual before buying; don’t guess from another GM Ecotec. Park level, set the brake, chock the rear wheels, and buy oil that explicitly says dexos1 on the bott...
2. **Warm briefly and protect the work area - Warm 2-3 minutes - warm, not hot. Gather a drain** pan, funnel, socket set, gloves, and the filter wrench matching your confirmed filter. Raise the front on ramps or stands for clearance and lay cardboard under the engine for drips.
3. **Drain the used oil and replace the filter - Remove the drain plug and drain to an** occasional drip. Locate the filter per your owner’s manual and position the drain pan underneath before loosening - filters hold oil and spill when tipped. Compare the new filter to the old (same siz...
4. **Install the correct oil quantity - Pour 5.0 quarts of 5W-30 dexos1 through a funnel,** adding the last quart slowly. Refit the cap and confirm the dipstick tube and filter area are clean and dry before starting.
5. **Check level, leaks, and service reminder - Start the engine, idle 30-60 seconds, and** check underneath for leaks at the plug and filter. Reset the oil life monitor through the dash menus or the accelerator-pedal procedure in your manual.

TORQUE

ezcarfix.com