2019-2024 Chevrolet Silverado 1500 - Change Oil

2019-2024 Chevrolet Silverado 1500 | Moderate | 45 minutes | $40 DIY

TOOLS

15mm Socket Flathead Screwdriver Jack Stands Oil Filter Wrench Drain Pan Torque Wrench Funnel

PARTS

Engine Oil (0W-20 Full Synthetic) $30.00
Oil Filter $10.00

STEPS

1. **Prepare (8.0 qt, 0W-20 Dexos1!) - 5.3L V8 (L82/L84): 0W-20 Dexos1 Gen2/Gen3 full** synthetic, 8.0 qt (7.6L) with filter - big sump, don't underfill. Need: 0W-20 Dexos1 (two 5-qt jugs), ACDelco PF63, large drain pan, funnel. Some 2019+ 5.3Ls consume oil (DFM) - check the...
2. **Drain the Old Oil - Position the large drain pan and remove the drain plug - expect a** full 8.0 quarts, so make sure the pan is big enough. If significantly less drains out, your 5.3L may be consuming oil (DFM-related); check the level regularly.
3. **Replace PF63 Filter - Remove the old PF63 spin-on filter. Install the new PF63 -** hand-tighten plus a quarter turn. Ensure the old gasket came off. Use the PF63, not a cheap generic - with 8 quarts of oil, the filter does important work.
4. **Reinstall Drain Plug (18 ft-lbs) - Reinstall the drain plug. Torque to 18 ft-lbs - use a** torque wrench; don't over-tighten the aluminum pan.
5. **Add 8.0 Quarts of 0W-20 - Add 8.0 quarts (7.6L) of 0W-20 Dexos1 full synthetic through** the filler cap. Use ONLY Dexos1-approved 0W-20 - the 5.3L has used 0W-20 since ~2013 (not 5W-30). Check the dipstick after filling.
6. **Check Level, Leaks, Reset Monitor - Start the engine and check for leaks at the drain** plug and filter. Run 30 seconds, shut off, recheck the level, and top up if needed. Reset the oil life monitor. Interval: 7,500 miles / 12 months (or per monitor).

TORQUE

Oil Drain Plug 24 Nm 18 ft-lbs

ezcarfix.com