2011-2015 Chevrolet Volt | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2011-2015 Chevrolet Volt $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - 1.4L range-extender: about 3.7** quarts dexos1 5W-30 with a new filter. Filter: spin-on (ACDelco PF65 / GM 55352643). Buy filter, oil, and a new washer. The gas engine may not have run for days - the oil is stone cold.
2. **Warm briefly and protect the work area - In Park, start the gas engine with Hold or** Mountain mode; run 3-5 minutes - you're starting stone cold. Power fully OFF. Wide pan; cardboard beneath. The bay is cramped - locate filter and plug with a flashlight first.
3. **Drain the used oil and replace the filter - Loosen plug; remove it by hand, pushing** inward so it doesn't fall into the pan. Drain to an occasional drip - cold-thick oil takes longer. Reinstall with a NEW washer; tighten to manual spec. Spin off the old filter upright.
4. **Install the correct oil quantity - Pour in 3.5 quarts of dexos1 5W-30. Wait full minute;** check the dipstick; add in small pours to 3.7 quarts. The dipstick is final - fill to the full mark, never above. Reinstall cap; lower the car to level ground.
5. **Check level and leaks - Wait 2-3 minutes; verify the dipstick twice - pull, wipe,** reinsert, read. Full mark, never above. Start (Hold/Mountain); idle 30-60 seconds; check for drips. Shut off; wait two minutes; confirm. Recycle the oil and filter free at any aut...

TORQUE

ezcarfix.com