# 2011-2017 Chrysler 200 - Engine Oil & Filter Change



**2011-2017 Chrysler 200 | Moderate | 30-60 minutes | $57 DIY**

**TOOLS**

Floor jack or ramps and rated jack stands if needed  Oil-drain pan, funnel, gloves, and eye protection  Socket or wrench for the drain plug and oil-filter tool
Calibrated torque wrench and shop towels

**PARTS**

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2011-2017 Chrysler 200 $12.00

## STEPS

1. **Confirm oil specification and make the vehicle safe - 2015-2017 200 2.4L Tigershark: 5.5** quarts of 0W-20 meeting Chrysler MS-6395, filter changed. The 2011-2014 2.4L takes 4.5 quarts of 5W-20; the 3.6L V6 takes 6.0 quarts of 5W-30 with a top-side cartridge - confirm engine and year.
2. **Warm briefly - Idle the 200 two to three minutes so the oil thins and drains fully, then** switch off. Remove the filler cap on the valve cover to vent the crankcase. Raise the front on ramps or jack stands to work underneath safely.
3. **Drain the used oil and replace the filter - Drain to a drip; refit with a fresh washer,** tightened firmly. On the 2.4L engines, the spin-on sits on the front of the block - spin it off, confirm the old gasket came away, oil the new gasket, install hand-tight plus three-quarters tur...
4. **Install the correct oil quantity - Pour 5.5 quarts of 0W-20 MS-6395 through a funnel into** the filler neck (4.5 quarts of 5W-20 for the 2.4L; 6.0 quarts of 5W-30 for the 3.6L). Refit the filler cap and wipe the valve cover.
5. **Check level and leaks - Start the engine and idle a minute so the new filter fills and** oil pressure builds; the oil light should go out quickly. Switch off, wait a few minutes, then recheck the dipstick and top up if needed.

## TORQUE

ezcarfix.com