

2015-2017 Chrysler 200 | Moderate | 45 minutes | \$30 DIY

TOOLS

10mm Socket Flathead Screwdriver Jack
Stands Phillips Head Screwdriver Needle
Nose Pliers

PARTS

9012 Halogen Headlight Bulb 9012 \$15.00
H11 Halogen Headlight Bulb H11 \$15.00

STEPS

- 1 Access the headlight bulb - Turn the lights off and open the hood. Locate the bulb access cover behind the headlight assembly. On some models you may need to move an air box, battery cover, or washer reservoir for hand access.**
- 2 Remove the access cover / socket - Twist the dust cover or bulb socket counterclockwise and remove it. Note the connector orientation before unplugging.**
- 3 Disconnect and remove the old bulb - Unplug the electrical connector. Release any retaining clip or twist the bulb carrier free, then pull the bulb straight out. Avoid forcing plastic tabs.**
- 4 Install the new bulb - Handle the new bulb with gloves or a clean cloth - skin oil on halogen glass shortens bulb life. Seat the bulb in the correct index tabs and secure the clip/socket.**
- 5 Reassemble and test - Reconnect the electrical connector, refit the dust cover, and restore any parts moved for access. Turn on low and high beams to verify both sides before closing the hood. Aim headlights if the beam pattern looks off.**