2013-2016 Dodge Dart - Engine Oil & Filter Change

2013-2016 Dodge Dart | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (0W-20) $45.00
Correct engine oil filter and drain-plug washer for 2013-2016 Dodge Dart $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - 2.0L Tigershark: 5.0 quarts of** 0W-20 meeting Chrysler MS-6395. 2.4L: 5.5 quarts of the same 0W-20; 1.4L turbo: 4.0 quarts of 5W-40 - confirm your engine, and check the bottle for MS-6395. Park level, brake set.
2. **Warm briefly and protect the work area - Raise the front on ramps or jack stands; slide a** 6+ quart pan underneath. The belly pan’s small access door (one screw) opens for the drain plug - don’t remove the whole pan.
3. **Drain the used oil and replace the filter - Drain to a drip; refit with a fresh washer.** 2.0L/2.4L: spin-on filter on the front of the block - spin it off, oil the new gasket, hand-tight plus three-quarters. 1.4L turbo: top-side cartridge housing (27mm cap) instead.
4. **Install the correct oil quantity - Pour 5.0 quarts of 0W-20 MS-6395 (5.5 for 2.4L; 4.0** quarts 5W-40 for 1.4L turbo). Add 4.5 quarts first, wait a minute, then top up to the full mark. Refit the filler cap and wipe the valve cover.
5. **Check level, leaks, and service reminder - Idle a minute; the oil light should go out** quickly. Switch off, wait a few minutes, recheck the dipstick. Check underneath for weeping; close the access door if opened. Reset the oil-life monitor.

ezcarfix.com

TORQUE