2013-2016 Dodge Dart - Wiper Blade Replacement

2013-2016 Dodge Dart | Easy | 10-15 minutes | $66 DIY

TOOLS
Microfiber cloth

PARTS
Driver wiper blade, 26" Bosch 26A $32.99
Passenger wiper blade, 18" Bosch 18B $32.99

STEPS

1. **Confirm the sizes and buy the blades - Buy blades that fit a small J-hook arm (9x3 on** most Darts; some 2013-2014 cars use a 9x4 hook, so check the adapter in the box).
2. **Park and prep - no service position needed - The Dart parks its wipers on the glass where** you can reach them, so there is no service position to set. Switch the ignition off and make sure the wiper stalk is off. Lift the driver-side arm until it holds away from the windshield.
3. **Release the old blade from the hook arm - Lift the driver-side arm until it stands off** the glass. Find the small release tab where the blade's adapter sits in the J-hook, press it, and slide the blade down out of the hook.
4. **Prep the new 26-inch blade - Remove the protective sleeve from the new blade and keep** your fingers off the rubber wiping edge. Compare the new blade to the old one to confirm the 26-inch length.
5. **Hook the new blade on and verify the lock - Slide the new 26-inch blade into the arm's** hook and rotate it up until the adapter clicks into place. Lower the arm back onto the windshield gently, guiding it down by hand than letting it drop.
6. **Install the 18-inch passenger blade - Repeat the tab-release and hook install for the** 18-inch passenger blade. This is where Dart owners most go wrong - double-check the 26-inch blade is on the driver side.
7. **Test with washer fluid - Start the car, spray washer fluid, and run the wipers on low and** high. A chattering blade means the adapter did not fully click into the hook - remove it and re-seat until you feel the positive lock.

TORQUE

ezcarfix.com