2012-2019 Fiat 500 - Engine Oil & Filter Change

2012-2019 Fiat 500 | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool
Calibrated torque wrench and shop towels
27mm Socket

PARTS

Engine Oil (5W-30) $45.00
Correct engine oil filter and drain-plug washer for 2012-2019 Fiat 500 $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - 1.4L MultiAir takes 4.0 quarts of** 5W-30. Cartridge element with fresh O-ring, drain pan, funnel, 27mm socket for the filter cap. Park level, brake set; raise the front on stands or ramps - never the jack alone.
2. **Warm briefly and protect the work area - Idle two to three minutes, then shut it off.** Twist off the oil filler cap and lift the dipstick slightly to vent the crankcase. Slide the drain pan under the oil pan and spread cardboard for drips.
3. **Drain the used oil and replace the filter - Spin the drain plug out by hand. Unscrew the** cartridge cap with the 27mm socket. Swap the cartridge and O-ring, oiled. Drain to a drip; thread the plug in by hand and snug it firmly.
4. **Install the correct oil quantity - Set a funnel in the Fiat 500’s filler neck and pour in** 4.0 quarts of full-synthetic 5W-30. Pour slowly and watch the markings as you go - it is easier to add a final half-quart than to drain an overfill.
5. **Check level, leaks, and service reminder - Idle a full minute watching for leaks, then** shut off and wait two minutes. Dipstick: wipe, reseat, read - top up if below full. Reset the service reminder. Recycle the used oil at any auto-parts store.

TORQUE

ezcarfix.com