2022-2024 Honda Civic 2.0L - Oil Change Complete

2022-2024 Honda Civic | Moderate | 45 minutes | $42 DIY

TOOLS

17mm Socket Flathead Screwdriver Jack Stands Oil Filter Wrench Drain Pan Ratchet Wrench Funnel Gloves Safety Glasses Shop Towels

PARTS

Engine Oil (0W-20 Full Synthetic) $30.00
Oil Filter $10.00
Drain Plug Washer $2.00

STEPS

1. **Prepare the Vehicle - The 11th-gen 2.0L (non-turbo) takes 0W-20 full synthetic, 4.4** quarts with filter (4.2L) - more than the 1.5T's 3.7 qt, so don't use the turbo's capacity. Need: 0W-20, Honda filter, new crush washer. Drain plug: 30 Nm (22 ft-lb).
2. **Lift and Secure the Vehicle - Raise the front of the Civic and support with jack stands.** Ensure it's level. Chock the rear wheels. Remove the undertray fasteners to access the drain plug and spin-on filter.
3. **Drain the Old Oil - Position the drain pan. Remove the drain plug (30 Nm / 22 ft-lb on** reinstall, new crush washer) and let the 4.4 quarts drain for 10-15 minutes - make sure your pan has capacity; the 2.0L holds more than the 1.5T.
4. **Replace the Oil Filter - Unscrew the old spin-on filter. Clean the mounting surface, oil** the new filter's gasket, and install hand-tight plus a quarter turn. The filter is the same as the 1.5T's - but the oil CAPACITY differs, so don't confuse the two engines' a...
5. **Reinstall the Drain Plug - Reinstall the drain plug with a NEW crush washer. Torque to 30** Nm (22 ft-lb). Wipe clean. Reinstall the undertray. The 2.0L's 4.4 qt capacity means you'll use more than a single 4-qt jug - have enough oil.
6. **Add New Oil and Verify - Lower to level ground and add 4.4 quarts of 0W-20 (not 3.7 -** that's the 1.5T). Dipstick at the upper mark. Start, run 30 seconds, shut off, wait 2 minutes, recheck. Check for leaks and reset the Maintenance Minder.

TORQUE

Oil Drain Plug 30 Nm 22 ft-lbs

ezcarfix.com