2003-2008 Honda Pilot - Cabin Air Filter

2003-2008 Honda Pilot | Easy | 15-20 minutes | $26 DIY

TOOLS
None required (glove box access)

PARTS
Cabin air filter $26.00

STEPS

1. **Locate the filter housing - Park your Honda Pilot and turn off the ignition. No tools are** typically required.
2. **Lower the glove box - Open the glove box and empty its contents. Detach the damper arm on** the right side if equipped. Lower the glove box fully to expose the filter housing cover behind it.
3. **Remove the old filter - Unclip the filter housing cover to reveal the cabin filter tray.** Slide the tray out of the housing. Remove the old cabin filter from the tray and note the airflow arrow direction. Vacuum any debris from the empty housing.
4. **Install the new filter - Place the new cabin filter into the tray, aligning it with the** airflow arrows pointing in the same direction as the old filter. Slide the tray back into the housing until it clicks into place.
5. **Reassemble the glove box - Reattach the filter housing cover, confirming the clips** engage. Swing the glove box back up and push until the side stops click into place. Reattach the damper arm. Close the glove box and verify smooth operation.
6. **Test and set reminder - Start the vehicle and run the fan on high. Confirm strong airflow** from the vents with no unusual noises. Set a reminder to replace the cabin filter in 12 months or 12,000 miles.

ezcarfix.com