2003-2009 Hummer H2 - Cabin Air Filter Replacement

2003-2009 Hummer H2 | Easy | 20-30 minutes | $19 DIY

TOOLS
None required; done by hand Trim tool (optional, if a clip resists)

PARTS
Cabin air filter (Hummer H2 2003-2009 fitment) $19.00

STEPS

1. **Park and empty the glove box - Park the H2, switch off the ignition, and turn the climate** blower fully off. Open the passenger door and empty the glove box completely. You need the glove box free to swing down out of the way.
2. **Lower the glove box past its stops - Open the glove box and locate the travel stops on** each side plus the damper arm. Squeeze the sides inward to clear the stops and unhook the damper, then lower the glove box gently.
3. **Locate and remove the filter door - Find the rectangular filter door on the HVAC housing,** as shown in the video's location segment. Release its clips or tabs and pull the door straight off. Set it aside; the end of the old cabin filter is now exposed.
4. **Slide out the old cabin filter - Grip the old filter and slide it straight out of its** slot, noting the direction of the airflow arrows printed on the frame. Compare it with the new filter to confirm the size matches.
5. **Check the new filter and its orientation - Check the new filter against the old one for** identical dimensions. Orient it so the airflow arrows point the same direction as the original, toward the blower motor. Correct orientation keeps dust and pollen from reaching the cabin.
6. **Install the new cabin filter - Slide the new filter into the housing channel, keeping it** flat so no pleat folds over. Push it fully home until its end sits flush with the housing face.
7. **Refit the filter door and glove box - Press the filter door back onto the housing until** its clips lock. Lift the glove box back up, re-engage the side stops, and reconnect the damper arm. Close the glove box and confirm it opens and latches normally.
8. **Test the blower and finish up - Start the engine and run the blower on every speed,** feeling for strong, even airflow from the vents with no rattling. The job is complete when airflow is strong and quiet and the musty odor is gone.

ezcarfix.com