

2010-2013 Kia Soul | Moderate | 30-60 minutes | \$55 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed
Oil-drain pan, funnel, gloves, and eye protection
Socket or wrench for the drain plug and oil-filter tool
Calibrated torque wrench and shop towels

PARTS

Correct engine oil and viscosity for 2010-2013 Kia Soul +; verify the owner-manual specification \$45.00
Correct engine oil filter and drain-plug washer for 2010-2013 Kia Soul + \$12.00

STEPS

- 1 Confirm oil specification and make the vehicle safe - Verify the exact engine, oil viscosity, capacity, filter, and drain-plug washer for the 2010-2013 Kia Soul +.** Park level, set the brake, chock wheels, and use ramps or rated jack stands if access requires lifting.
- 2 Warm briefly and protect the work area - Run the 2010-2013 Kia Soul + only long enough to make the oil flow, then switch it off and wait briefly.** Remove the oil fill cap, place a drain pan, and keep oil off tires and the ground.
- 3 Drain oil and replace filter - Remove the drain plug carefully, let the 2010-2013 Kia Soul + drain fully, replace the washer if required, and install the new filter with a lightly oiled gasket using the exact procedure.**
- 4 Install correct oil quantity - Reinstall the drain plug to the exact engine-specific torque and add the specified oil through a funnel.** Do not guess capacity or overfill.
- 5 Check level, leaks, and reminder - Start the 2010-2013 Kia Soul + briefly, switch it off, wait, and recheck the level on level ground.** Inspect for leaks and record date and mileage.

TORQUE