2019-2024 Land Rover Range Rover Evoque | Easy | 15-30 minutes | $26 DIY

TOOLS
Small flat screwdriver or trim tool
Vacuum or damp cloth Flashlight

PARTS
Cabin air filter (MANN CUK 2733 / LR056138, activated carbon) $25.55

STEPS

1. **Empty the glovebox and prepare - Park the Evoque, switch the ignition off, and open the** passenger-side front door. Empty the glovebox completely so it can lower without spilling. Note how the glovebox sits before you touch it so reassembly is straightforward.
2. **Lower the glovebox to expose the filter cover - Release the glovebox (side stops or** damper arm, depending on trim) and let it swing down fully, supporting it so it doesn't hang by the damper cord. The rectangular filter access cover should now be visible.
3. **Remove the filter cover and old filter - Unclip or unscrew the filter access cover and** set it aside. Note the airflow arrows on the old filter's frame before pulling it out. Slide the old filter out level so trapped debris doesn't spill into the housing.
4. **Clean the filter housing - Vacuum or wipe out the filter housing to remove leaves, dust,** and debris around the old filter. Check the housing for dampness, which can indicate a clogged cowl drain worth clearing.
5. **Install the new filter correctly oriented - Slide the new filter in with the airflow** arrows matching the old one - on the Evoque, downward toward the blower. Seat it fully flat with no edge gaps, then refit the access cover until its clips engage positively.
6. **Reassemble and test the HVAC - Swing the glovebox back up, re-engage the side stops and** damper arm, and confirm it opens and closes smoothly. Return the contents and run the climate on fresh-air a minute. Confirm strong, clean airflow from the vents.

ezcarfix.com