2019-2024 Land Rover Range Rover Evoque - Engine

2019-2024 Land Rover Range Rover Evoque | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels 64-65mm 14-Flute Wrench

PARTS

Engine Oil (0W-20) $45.00
Correct engine oil filter and drain-plug washer for 2019-2024 Land Rover Range Rover Evoque $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - Watch the model year on this one:** the 2019 Evoque 2.0T takes 6.4 quarts of 5W-30, while 2020 and newer take 5.1 quarts of 0W-20, and both must meet Jaguar Land Rover’s STJLR.03.5006 spec. The filter is a cartridge (Land Rover LR073669 or e...
2. **Warm briefly and protect the work area - Raise the front onto ramps or rated jack stands** and remove the engine under-shield to reach the sump and filter housing. Open the fill cap to help the drain, and keep a rag handy - the cartridge housing always dribbles a little.
3. **Drain the used oil and replace the filter - Remove the drain plug and drain fully. Up** top, unscrew the filter housing cap with the 64-65mm 14-flute wrench, lift the cap out with the old cartridge attached, and pull the element off. Fit the new element into the housing. Don’t overtig...
4. **Install the correct oil quantity - Reinstall the drain plug with a new washer at 15 lb-ft** (20 Nm). Pour in the year-correct quantity, 6.4 quarts for a 2019 or 5.1 quarts for 2020 and up, through a funnel, then verify the level on the dipstick and adjust without overfilling....
5. **Check level, leaks, and service reminder - Start the engine and idle briefly, checking** for leaks at the drain plug and the filter housing. Refit the under-shield with all its fasteners. Recheck the oil level once the engine has run and settled, record the date and mileage, and rese...

TORQUE

ezcarfix.com