2019-2024 Lexus UX - Wiper Blade Replacement

2019-2024 Lexus UX | Easy | 10-15 minutes | $81 DIY

TOOLS

A soft towel to protect the glass Glass cleaner and a lint-free rag A small flat screwdriver, only for a stubborn hook tab

PARTS

Driver wiper blade, 26" Bosch 26A $32.99
Passenger wiper blade, 16" Bosch 16B $32.99
Rear wiper blade, 12" $14.99

STEPS

1. **Buy 26 and 16 up front, 12 for the hatch glass - The UX takes 26 (driver), 16** (passenger), and 12 inches (rear hatch glass). Front arms are standard J-hooks - most beam blades fit; the rear uses a small pivot-clip mount. Lexus also sells rubber inserts alone - refills if your blade f...
2. **Raise the wipers into service mode - Blades park tucked under the hood’s back edge - use** service mode: power ON then fully OFF; within 45 seconds hold the wiper lever in MIST for 2+ seconds so the wipers rise and stop upright. Switch the wipers fully OFF before handling the...
3. **Unclip the driver’s 26-inch blade from its hook - Lift the driver’s arm, towel** underneath. Squeeze the locking tab where the clip wraps the J-hook, rotate the blade 90 degrees, and slide it off. Keep your grip - the long driver’s-arm spring is strong.
4. **Click the new driver blade on and tug-test it - Thread the blade’s adapter through the** hook’s open end, swing it in line with the arm, and press until the tab clicks. Tug along the arm to confirm seating, then lower the arm slowly - never let the spring slam it.
5. **Fit the 16-inch passenger blade - Fit the 16-inch blade on the passenger side - same** hook, tab, and click. Check the box length first; the two fronts get mixed up constantly. Tug-test, lower the arm gently, then confirm the 26 sits driver-side and the 16 passenger-side.
6. **Unsnap the 12-inch rear blade and fit its replacement - Hold the short, stiff rear arm** firmly. Pull the 12-inch blade past its stop until it clicks free; lift it off. Press the new blade onto the pivot until it snaps flush and swings freely, then lower the arm gently.
7. **Test all three blades and plan on yearly replacement - Power on; run front washers, then** rear. All three blades should sweep fully, quietly, streak-free; cycle intermittent and low, and confirm the rear parks straight. Replace yearly - the big driver blade and sun-baked rear blade wear faste...

TORQUE

ezcarfix.com