2019 Mazda 3 - Check Engine Light: Most Common

2019 Mazda 3 | Easy | 30-60 minutes | $100 DIY

TOOLS

OBD2 scanner (Bluetooth dongle plus a smartphone app, or a handheld code reader)
Pen and paper or your phone, to record the exact codes and freeze-frame data
Flashlight, to see the OBD-II port under the dash

PARTS

BlueDriver Bluetooth Pro OBD2 Scan Tool LSB2 $100.00

STEPS

1. **Steady light or flashing light? - A steady light means a fault is stored but the car is** safe to drive cautiously. A FLASHING light means an active misfire that can overheat and ruin the catalytic converter: ease off the gas, pull over when safe, and have the car towed.
2. **Check the stall recall first, before spending anything - 2019 Mazda3 cars built September** 25, 2018 through May 11, 2019 with the 2.5L engine and cylinder deactivation are covered by Mazda recall 3719F (NHTSA 19V497). A PCM software error when switching out of cylinder-deactivation mode can let a...
3. **Check the gas cap - If the light came on after fueling, refit the cap until it clicks. A** loose, cracked, or missing cap lets fuel vapor escape and sets evaporative-emissions codes. It can take several drive cycles (up to a few days) for the light to clear.
4. **Scan for codes and write them all down - Plug an OBD2 scanner into the 16-pin port under** the driver's side dashboard, switch the ignition to ON without starting the engine, and read the codes. Write down every code exactly, plus any freeze-frame data (the sensor snapshot from whe...
5. **Match the code to the cause - P0300 (random misfire) on this car points first at the** recall above, then at worn spark plugs or a failing ignition coil. P0171 (system too lean) usually means unmetered air entering after the mass airflow sensor: a loose intake duct, a va...
6. **Check the battery - A weak battery can leave spurious codes stored. Inspect the terminals** for corrosion and tightness, and check the battery holds charge. If the car runs normally after a jump start, record the codes first, then have the battery and charging...
7. **Fix the cause, then clear and verify - Only clear codes after the underlying repair or** dealer recall reprogram. Drive normally through several trips: if the same code returns, the fault is real. A code that returns immediately at startup is a hard fault; one that takes days to...
8. **Know when to stop and get professional diagnosis - Stop DIY diagnosis and book a shop or** dealer if the light flashes, the engine stalls or will not restart, the engine overheats, or an oil-pressure or coolant-temperature warning joins the check engine light. A professional diagnosis typica...

ezcarfix.com