2004-2009 Nissan Quest - Cabin Air Filter

2004-2009 Nissan Quest | Easy | 20-30 minutes | $28 DIY

TOOLS

Phillips screwdriver (for the glove box screws and the three microfilter cover screws) Flashlight (to find the cover and read the airflow arrows) Shop vacuum or small brush (to clean the housing slots) Small cup or tray (to keep the screws together)

PARTS

Cabin air filters (pair) for 2004-2009 Nissan Quest; verify arrows, size, and VIN/trim fitment $28.00

STEPS

1. **Empty the glove box and remove the glove box assembly - The Quest's cabin filters sit** inside the front heater and cooling unit behind the glove box, so the glove box assembly has to come out first. Open the glove box, empty every item from it, then locate the screws securing the glove box to th...
2. **Locate the in-cabin microfilter cover - This is the in-cabin microfilter cover. It is** held in place by three small screws.
3. **Remove the three screws and lift off the filter cover - Using a Phillips screwdriver,** back out the three screws securing the microfilter cover. They are small and drop easily, so hold your free hand under the cover as the last screw comes out. Lift the cover away from the housing and set it on...
4. **Slide out the two stacked microfilters - The Quest uses two thin microfilters stacked one** on top of the other, inserted sideways into the heater and cooling unit. Pull the first filter straight out toward you; it may drag slightly on the housing guides, which is normal. Once the...
5. **Clean the filter housing slots - With both filters out, inspect the two narrow slots in** the heater and cooling unit. Check the rubber sealing edges on the cover for cracks or compression - a damaged seal lets unfiltered air bypass the filters and dump straight onto the...
6. **Install the two new filters with arrows aligned - Slide the new lower filter in first,** then the upper one, stacking them one above the other exactly as the old pair sat. Confirm the airflow arrow on the side of each new filter points the same direction as the arrows on the filters you rem...
7. **Reinstall the glove box and verify the HVAC - Refit the glove box assembly, reinstall all** of its screws, and check that the glove box door opens, closes, and latches squarely. Start the engine and run the climate system on high through every vent mode - dash, floor, and defrost -...

TORQUE

ezcarfix.com