2014-2015 Nissan Rogue Select - Cabin Air Filter

2014-2015 Nissan Rogue Select | Easy | 10-15 minutes | $28 DIY

TOOLS

No tools required - hands only Flashlight (optional, the footwell is dark)

PARTS

Cabin air filter for 2014-2015 Nissan Rogue Select; verify arrows, size, and VIN/trim fitment Fram CF10550 $28.00

STEPS

1. **Park and open up the passenger side - Park on level ground, ignition off, and open the** front passenger door. Slide the passenger seat all the way back. You do not need to drop the glove-box door the way you would on the newer second-generation Rogue.
2. **Pull off the front foot/kick panel - Look at the kick panel closest to the front of the** vehicle, just below the glove box. Grip it and pull it straight out toward you. Pull evenly across the panel so the clips release together instead of snapping one off.
3. **Find the filter cover and pull its ring - Behind where the panel was, on the passenger** side of the big black HVAC housing, you will see a rectangular filter access door. It has a pull ring on its front face. Hook a finger through the ring and pull.
4. **Note the arrow, then slide the old filter out - Before you touch the filter, look at the** airflow direction arrow printed on its exposed edge and memorize which way it points. Then grab the edge of the filter and slide it straight out of the housing.
5. **Slide the new filter in, arrow matched - Slide the new filter into the housing in the** same orientation, with its airflow arrow pointing the same direction the old one's did. Push it all the way home until it sits flush; a half-inserted filter is the usual cause of whistling vents...
6. **Refit the filter cover and tug-test the panel - Press the filter cover back on - ring** facing out - until it clicks into the housing. Give the panel a light tug to confirm nothing is loose.
7. **Run the fan and listen - Start the car and run the blower from low to high, then switch** to recirculation. Airflow should be strong and even, with no whistle or rattle from under the dash. Pull the panel and reseat it.

TORQUE

ezcarfix.com