2019-2024 Ram 3500 - Cabin Air Filter Replacement

2019-2024 Ram 3500 | Easy | 15-20 minutes | $28 DIY

TOOLS

Flashlight Clean rag for clearing debris from the housing mouth

PARTS

Cabin air filter for 2019-2024 Ram 3500; verify arrows, size, and VIN/trim fitment
$28.00

STEPS

1. **Empty the glove box and lower it - Open the glove box and take everything out of it.** Check for a damper cord or arm on the side and unhook it if it resists the drop.
2. **Locate the HVAC filter door - Take a flashlight and look at how the door is latched or** clipped so you can release it without forcing anything. Note the door's orientation; it only goes back one way.
3. **Open the filter door and pull the old filter - Release the door's latches or clips and** pull it away from the HVAC case. Slide the old filter straight out of its slot. Check the airflow arrow printed on the old filter's frame and note its direction before you discard it.
4. **Inspect the housing and check the seals - Before the new filter goes in, look into the** open slot with a flashlight and pull out any leaves, straw, or debris with your fingers or a rag.
5. **Install the new filter in the correct orientation - Slide the new filter into the slot** with the airflow arrow pointing in the same direction as the old one. Keep the filter flat going in; if a pleat folds over at the entrance, pull it back out and restart the slide.
6. **Close the filter door - Seat the filter door back onto the HVAC case and engage its** latches or clips fully; a door that is not latched will rattle over bumps and leak air.
7. **Run the HVAC and confirm clean, quiet airflow - Start the truck and run the HVAC on high** fan speed with fresh-air mode selected. Check this filter more than a car filter if the truck sees dusty roads or job sites; a clogged filter shows up first as weak defroster and a musty smell.

TORQUE

ezcarfix.com