2007-2011 Toyota Camry - Cabin Air Filter

2007-2011 Toyota Camry | Easy | About 10 minutes | $35 DIY

TOOLS

No tools required (glove box, damper, and filter cover all release by hand) Dry rag (to wipe the housing rim before opening the cover)

PARTS

Cabin Air Filter CF10285 $20.00
Glove Box Support Rod $5.00
Glove Box Damper $10.00

STEPS

1. **Set the HVAC to recirculate - With the ignition on, set the climate control to** recirculate mode, then turn the ignition off.
2. **Drop the glove box - Open the glove box and empty it. On the right side you will see the** damper with a retainer clip - pull the clip toward you to free the damper. No tools are involved at any point in this job.
3. **Open the filter cover - Behind the glove box is the rectangular cabin filter cover with a** clip on each side. Pinch both clips inward and pull the cover straight off.
4. **Pull the old filter - Slide the old filter straight out of its case. Look at the airflow** indicator on its edge and remember the direction - Toyota prints the arrow on the Camry's filter to point down when installed.
5. **Drop in the new filter - Unwrap the new filter and slide it into the case with the** airflow indicator pointing down, exactly as the old one sat.
6. **Reinstall the cover - Set the cover back over the housing and press until both side clips** snap home. A cover that sits crooked will whistle at highway fan speeds, so press each clip individually and feel for the click before moving on.
7. **Note the service interval - Plan on doing this once a year, or every 12,000 to 15,000** miles if you drive in dusty areas.

ezcarfix.com