2017-2018 Toyota Yaris iA - Engine Oil & Filter

2017-2018 Toyota Yaris iA | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (0W-20) $45.00
Correct engine oil filter and drain-plug washer for 2017-2018 Toyota Yaris iA $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - The Mazda-built Yaris iA’s 1.5L** Skyactiv-G takes 0W-20 only, 4.4 US quarts with a new filter. The spin-on filter is the Mazda PE01-14-302 family - Toyota dealers may not stock it, so ask for it by the Mazda number.
2. **Warm briefly and protect the work area - Stage the spin-on filter, a filter wrench, a** drain pan, and the washer. Idle the Yaris iA two to three minutes to warm the oil, then shut it off and wait briefly.
3. **Drain the used oil and replace the filter - Reach the spin-on filter from underneath,** loosen it with the wrench, and confirm the old gasket came off with the canister. Lightly oil the new filter’s gasket and install hand-tight plus a quarter turn.
4. **Install the correct oil quantity - Pour 3.9 of the 4.4 quarts of 0W-20 through a funnel** and hold back the last half quart. Wait a few minutes, then check the dipstick.
5. **Check level, leaks, and service reminder - Start the Yaris iA briefly, switch it off,** wait two minutes, and recheck on level ground, topping to the full mark. Inspect the plug and filter base for leaks and reset the maintenance reminder through the cluster menu. Log the date, milea...

TORQUE

ezcarfix.com