2019-2023 Volkswagen Arteon - Engine Oil & Filter

2019-2023 Volkswagen Arteon | Moderate | 30-60 minutes | $57 DIY

TOOLS

Floor jack or ramps and rated jack stands if needed Oil-drain pan, funnel, gloves, and eye protection Socket or wrench for the drain plug and oil-filter tool Calibrated torque wrench and shop towels

PARTS

Engine Oil (0W-30 or 0W-20) $45.00
Correct engine oil filter and drain-plug washer for 2019-2023 Volkswagen Arteon $12.00

STEPS

1. **Confirm oil specification and make the vehicle safe - The 2.0T takes 5.7 litres (about 6** quarts) of 0W-30 meeting VW 504 00. Cartridge filter in a top-mounted EA888 housing. Check the drain plug type: plastic twist-lock (flat-head until it clicks) or metal. Have a cap wrench, pan, funnel.
2. **Warm briefly - Warm briefly, shut off, let it sit a few minutes. Lift onto ramps or** stands - never a jack alone - and remove the under-shield. Open the fill cap; keep a rag handy - the cartridge housing always dribbles.
3. **Drain the used oil and replace the filter - Remove the drain plug; drain fully. Unscrew** the housing cap, swap the cartridge, and oil the new O-ring into the cap groove. Thread the cap on by hand, then torque to 25 Nm - never force the plastic threads.
4. **Install the correct oil quantity - Reinstall the drain plug - metal torques to 30 Nm,** plastic twist-lock just clicks home. Pour in 5.7 litres of 0W-30 through a funnel, adding the last half litre slowly and checking the dipstick to land on the full mark.
5. **Check level, leaks, and service reminder - Idle briefly, checking for leaks at the plug** and housing. Refit the under-shield with all its fasteners. Recheck the oil level after a few minutes, record the date and mileage, and reset the service interval through the cluster.

TORQUE

ezcarfix.com