

2018-2024 Volkswagen Atlas | Moderate | 30-45 minutes | \$45 DIY

TOOLS

Jack and jack stands (or ramps) Oil drain pan Socket set / wrench Oil filter wrench Torque wrench Funnel Rubber gloves Safety glasses Rags

PARTS

Engine Oil (correct viscosity / full synthetic) \$35.00
Oil Filter \$12.00
Drain Plug Crush Washer \$3.00

STEPS

- 1 Prepare the vehicle - Park the 2018-2024 Volkswagen Atlas on level ground, set the parking brake, and warm the engine 2-3 minutes so oil flows. Gather oil, filter, washer, and tools. Informational DIY - EZ Car Fix is not a shop.**
- 2 Lift and support safely - If needed, jack the 2018-2024 Volkswagen Atlas at factory points and support with jack stands (or use ramps). Never work under a vehicle held only by a jack.**
- 3 Drain the oil - Place the drain pan under the 2018-2024 Volkswagen Atlas oil pan, remove the drain plug, and let the oil drain fully. Inspect the plug threads and replace the crush washer.**
- 4 Replace the oil filter - Remove the old filter on the 2018-2024 Volkswagen Atlas, lightly oil the new filter gasket, and install hand-tight only. Do not use a wrench to finish the filter.**
- 5 Refit drain plug and refill - Reinstall the drain plug on the 2018-2024 Volkswagen Atlas and torque to spec (~25 ft-lbs / check manual). Lower the vehicle, then add the correct oil type/amount through the fill cap using a funnel.**
- 6 Check for leaks and reset - Start the 2018-2024 Volkswagen Atlas, check for leaks under the engine, verify oil level on the dipstick/electronic gauge, and reset the oil-life monitor per the owner's manual.**

TORQUE

Oil Drain Plug 34 Nm 25 ft-lbs
Oil Filter (hand-tight only)