2018-2024 Volkswagen Atlas - Replace Wiper Blades

2018-2024 Volkswagen Atlas | Easy | 15 minutes | $81 DIY

TOOLS

Flathead Screwdriver 10mm Socket
Ratchet Wrench Pry Tool Measuring Tape

PARTS

Driver wiper blade, 26" Bosch 26A $32.99
Passenger wiper blade, 22" Bosch 22B $32.99
Rear wiper blade, 12" $14.99

STEPS

1. **Service position (if needed) - The 2018-2024 Atlas needs service position - they park** tucked under the hood edge. Ignition on, then off, pull the wiper stalk down within about 10 seconds to park the arms upright. Never force the arms up from parked.
2. **Lift the wiper arm - With the arms in service position, lift one arm off the glass until** it stays up and slide a folded towel underneath. Never let a bare spring-loaded arm snap back onto the windshield. Work one side at a time.
3. **Release the old blade - The Atlas uses a 16mm top-lock connector: press the release** button on the blade connector and slide the blade off. Note the orientation - the replacement goes back the same way. Pull straight along the arm; never twist sideways.
4. **Match the new blade - The 2018-2024 Atlas takes a 26-inch driver-side and 22-inch** passenger-side blade, plus an 11-inch rear blade (some catalogs list 12 - measure the old one). Confirm the correct top-lock adapter and match the old blades' length.
5. **Install until it clicks - Slide the new blade onto the arm until the top-lock clicks,** then tug gently to confirm it's locked. The 26-inch blade goes driver side, the 22-inch passenger side. Check each blade lies flat with the rubber edge facing the glass.
6. **Lower and repeat - Lower each arm onto the glass, repeat on the other side, and fit the** rear blade. Exit service position and run both wash cycles. A top-lock blade not fully clicked rides at the wrong angle - reseat it.

ezcarfix.com